



- Meets the requirements of - US FDA 21 CFR 172.878 & 21 CFR 178.3620(a)

Sr. No.	Test Parameters	Unit	Test Method	Specification	
				Min.	Max.
1.	Appearance		Visual	Colorless, transparent, bright and clear oily liquid.	
2.	Color	Saybolt	ASTM D 156	+25	-
3.	Density at 25 °C	Gm/ ml	ASTM D 1298	0.820	0.850
4.	Kinematic Viscosity at 40 °C	cSt	ASTM D 445/ D 7042	12.0	16.0
5.	Flash Point, (COC)	°C	ASTM D 92	150	
6.	Pour Point	°C	ASTM D 97	-	- 15

Technical Grade White Oil L 85 is a light white oil formulated from highly refined hydrotreated base oils which is colorless, tasteless and odorless. It meets US FDA 21 CFR 178.3620 (b) requirements for (+25) Saybolt color & UV absorbance.

Application: Technical Grade White Mineral Oil is suitable for use in process requiring clear white oils. They find extensive usage in textile processing (non staining lubrication) , incense & perfume manufacture, plastic, paper and cosmetic industries, several oil based formulations, hair oils, hair lotions, shoe polish and petroleum jelly manufacturing industries.

Packing: HDPE Drums, Mild Steel Drums, Flexi Bag & IBC Container

Email: info@lodhabetro.com , exports@lodhabetro.com

Product Image:



Disclaimer: We make no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.