



White Oil Technical/ Cosmetic Grade

Technical Specification

Test Description	Test Method	Specification Limits								
		WOT 60	WOT 70	WOT 80	WOT 100	WOT150	WOT 180	WOT 250	WOT 350	WOT 500
Appearance	Visual	Transparent clear, colourless, odourless liquid free from suspended impurities								
Colour, Say bolt	ASTM D 156	+30								
Density @ 25 °C, gm/ml	ASTM D 1298	> 0.810	> 0.8 20	> 0.822	>0.828	>0.830	>0.835	>0.835	>0. 850	>0.86 0
Kin. Viscosity @ 40 °C, cSt	ASTM D 445	07-Nov	Nov-14	14 - 17	19-23	27 - 33	30 – 35	36 – 45	68 – 72	80 – 85
Flash Point ° C min	ASTM D 92	145	150	160	180	180	190	190	200	220
Pour Point, °C, max	ASTM D 97	-15	-15	-15	-12	-12	-12	-12	-12	-12

Technical Grade White Oil M 150 is a white oil formulated from highly refined hydro treated base oils which is colourless, tasteless and odourless. It meets US FDA 21 CFR 178.3620 (b) requirements for (+25) Saybolt colour & UV absorbance.

Application: Technical Grade White Mineral Oil is suitable for use in process requiring clear white oils. They find extensive usage in textile processing (non staining lubrication), incense & perfume manufacture, plastic, paper and cosmetic industries, several oil based formulations, hair oils, hair lotions, shoe polish and petroleum jelly manufacturing industries.

Packing: HDPE Drums, Mild Steel Drums, Flexi Bag & IBC Container

Email: info@lodhapetro.com , exports@lodhapetro.com

Product Image:



Disclaimer: We make no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the products for the application contemplated by the user is solely their responsibility.

LODHA PETROCHEM

301, Shalibhadra Tower, Near Naranpura Railway Crossing, Naranpura, Ahmedabad – 380013, Gujarat, India
 Email: info@lodhapetro.com , exports@lodhapetro.com , | Website: www.lodhapetro.com www.lodhachem.com
 Mobile: 0091 – 9537131331, | Skype: [Lodha Petrochem](https://www.skype.com)